

## Day & Night Indoor 1.3MP/2MP IP Camera

### Features:

- ★ H.264 High Profile compression.
- ★ IP66 weatherproof aluminum 3-axis housing for indoor use.
- ★ Built-in 30 units of high efficiency IR LED.
- ★ Auto / Manual Electronic Shutter.
- ★ 3D Noise Reduction (3DNR).
- ★ Built-in ICR for true day & night without focus shift.
- ★ Support Dual Stream (1~25/30fps adjustable).
- ★ ONVIF version 2.0 compatible.
- ★ Support 3G Symbian, iPhone, Windows Mobile, Blackberry, Android Phone.
- ★ Support multiple browser: IE, Chrome, Firefox, Safari.



### Specifications:

Model No.	HIT13IP-O20F	HIT2IP-O20F
<b>Camera</b>		
CMOS Image Sensor	1/3" Aptina 1.3MP	1/2. 7" SONY 2MP
Effective Pixels (HxV)	1280x960	1920x1080
Elec. Shutter Speed	Auto / Manual: 1/50~1/10,000	
Minimum Illumination	Color: 0.1LUX / F1.2; 0LUX / IR	
S/N Ratio	More than 50 dB	
Gain Control	Auto / Manual	
BLC	Yes	
Day & Night	Auto (ICR) / Color / B&W	
IR LED	30 Units of 850nm H.E. IR LED	
IR Projection Distance	20 Meters	
White Balance	Auto	
Noise Reduction	3DNR	
Privacy Masking	4 Areas (Max.)	
Slow Shutter	None / Low / Middle / High	
Motion Detection	22x18 Areas	
Lens Furnished	3MP Board Lens 3.6mm / F1.2	
Power Supply	DC12V & PoE (802.3af) / 6W (Max.)	
Operating Temp.	-10°C to 50°C (14°F to 122°F)	
Housing Material	Metal IP66 Weatherproof	
<b>Video</b>		
Compression	H.264 High Profile / JPEG Snapshot	
Resolution	1280x720	1920x1080
Main Stream	1280x960 / 1280x720	1920x1080 / 1280x720
Sub Stream	704x576	
<b>Network</b>		
Ethernet	RJ-45 (10/100 Base-T)	
Protocol	IPv4, HTTP, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Cloud	
ONVIF	Vision 2.0 Compatible	
User Access	10 Users (Max.)	
3G / GPRS	Symbian, iPhone, Windows Mobile, Blackberry, Android Phone	
Browser	IE, Chrome, Firefox, Safari	

Design and specifications are subject to change without notice.